

**Title:** CU Tether Lifting System (TLS)

**Author:**

**Ludovic Bariteau**, [ludovic.bariteau@colorado.edu](mailto:ludovic.bariteau@colorado.edu), <https://orcid.org/0000-0001-9451-435X>

Associate Scientist

National Oceanic and Atmospheric Administration (NOAA)  
Cooperative Institute for Research in Environmental Sciences (CIRES)  
325 Broadway Av, R/PSDN  
Boulder, CO, 80305  
voice: 303/497-4482  
email: [ludovic.bariteau@colorado.edu](mailto:ludovic.bariteau@colorado.edu)

For a DOI, the author list should include Julie Lundquist ([julie.lundquist@colorado.edu](mailto:julie.lundquist@colorado.edu), <https://orcid.org/0000-0001-5490-2702>), Nicola Bodini ([Nicola.Bodini@colorado.edu](mailto:Nicola.Bodini@colorado.edu), <https://orcid.org/0000-0002-2550-9853>), Jessica Tomaszewski ([Jessica.Tomaszewski@colorado.edu](mailto:Jessica.Tomaszewski@colorado.edu), <http://orcid.org/0000-0002-1043-9901>), Laura Mazzaro ([Laura.Mazzaro@colorado.edu](mailto:Laura.Mazzaro@colorado.edu), <http://orcid.org/0000-0003-3438-376X>), and Patrick Murphy ([pamu5248@colorado.edu](mailto:pamu5248@colorado.edu), <http://orcid.org/0000-0002-5310-1564>)

## 1.0 Data Set Overview:

The CU Tether Lifting System was deployed within the valley at the lower “Orange” site during the IOP period (1 May – 15 June 2017).

It was located at:

Site	PT-TM06/ETRS89 x (more accurate)	PT-TM06/ETRS89 y (more accurate)	Latitude (less accurate)	Longitude (less accurate)	Elevation (msl)
Lower Orange	33981.840	5004.066	39.712652°	- 7.736823°	298.404

Note that the more accurate PT-TM06 and elevation readings listed in the table above should be considered authoritative.

## 2.0 Instrument Description:

The University of Colorado at Boulder’s tethered lifting system (TLS) is a specialty-designed state-of-the art tethersonde that offers unique high resolution and highly sensitive in situ measurements of wind speed and direction, temperature, and TKE dissipation rate (Frehlich et al., 2003). When used in profiling mode, the TLS can collect continuous high-resolution profiles from the surface up to heights of several hundred

meters. The TLS capabilities for observing detailed mean wind speed and temperature profiles, as well as turbulence dissipation rates, is proven in numerous field experiments (Balsley et al., 2003; Frehlich et al., 2003).

The setup for PERDIGAO will be described in an upcoming paper (Bariteau 2018) but the current payload is similar to that used in the Turbine Outflow and Dissipation Study (TODS) field campaign in Fall 2012 (Lundquist and Bariteau 2015), including 1.25 mm length and 5  $\mu$ m diameter Tungsten wires for 1 kHz hotwire anemometer velocity measurements and 1 kHz coldwire temperature measurements (Auspex Scientific, custom-made), 100 Hz thermistors (Honeywell 111-103EAJ-H01) and solid-state measurements for temperature (Analog Devices Inc TMP36) and relative humidity (Honeywell HIH-4000), a 100 Hz pitot tube (Dwyer instruments model 166-6) and pressure sensor (Honeywell DC001NDC4) for velocity and pressure measurements, as well as GPS and compass measurements. The GPS measurements of latitude, longitude, and altitude are sampled every 5 seconds and are estimated to have a positional error of less than 5 m by the manufacturer. A Vaisala T/RH probe (Vaisala HMP77 probe) was setup near the winch and was used as an independent verification point to correct the T/RH sensors when necessary.

### 3.0 Data Collection and Processing:

The turbulent payloads were suspended below a Helikite (Allsopp inc., UK) lifting platform tethered to a winch located at the lower Orange site (Figure 1 and 2)



Figure 1: CU TLS with winch, helikite and base setup at lower orange site.



*Figure 2: CU TLS with suspended turbulent payload in profiling mode.*

The hotwire anemometer is calibrated with respect to the pitot tube previously calibrated at NCAR wind tunnel. The coldwire anemometer data are calibrated with respect to a small bead thermistor sensor calibrated against a solid-state sensor. We follow techniques similar to Frehlich et al., 2008.

Basic outliers removal and quality control has been applied to these data set, but they will be subject to revisions.

#### **4.0 Data Format:**

100Hz Data have been saved in tab delimited ASCII text files. Missing data are denoted as NaN. This is the first version of the data, March 21, 2018. Filenames are as follow MMDDYYYY\_HHMMUTC.txt with MM the month, DD the day, YYYY the year, and

HHMM the starting time of data collection. Each file contains one header line and eight columns as follow:

- 1) Day-Of-Year
- 2) Altitude (m).
- 3) Latitude (decimal degrees)
- 4) Longitude (decimal degrees)
- 5) Barometric pressure (mbar)
- 6) Air temperature from the coldwire (C)
- 7) Relative Humidity (%)
- 8) Wind speed from the hotwire anemometer (m/s)

#### **5.0 Data Remarks:**

Sometimes the GPS had issues so the altitude was replaced by the geopotential height for a few instances.

#### **6.0 References:**

Balsley, B. B., Frehlich, R. G., Jensen, M. L., Meillier, Y. and Muschinski, A.: Extreme Gradients in the Nocturnal Boundary Layer: Structure, Evolution, and Potential Causes, *J. Atmospheric Sci.*, 60(20), 2496–2508, doi:10.1175/1520-0469(2003)060

Bariteau et al., 2018, Turbulence measurements from the TLS during PERDIGAO: Overview, results, and future capabilities, *Atmos. Meas. Tech.*, in preparation.

Frehlich, R., Meillier, Y., Jensen, M. L. and Balsley, B.: Turbulence Measurements with the CIRES Tethered Lifting System during CASES-99: Calibration and Spectral Analysis of Temperature and Velocity, *J. Atmospheric Sci.*, 60(20), 2487–2495, doi:10.1175/1520-0469(2003)060

Lundquist J K and Bariteau L 2015 *Bound. Layer Meteorol.* **154** 229-241