#### **TITLE**

CAMP Tibet BJ-SMTMS 20021001 20030331.stm

#### **CONTACT**

Nozomu Hirose

Depertment of Civil Engneering, University of Tokyo 7-3-1 Hongo, Bunkyoku, Tokyo, 113-8656 Japan

Phone: +81-3-5841-6107 Fax: +81-3-5841-6130

Email: hirose@hydra.t.u-tokyo.ac.jp

Toshio Koike

Depertment of Civil Engneering, University of Tokyo 7-3-1 Hongo, Bunkyoku, Tokyo, 113-8656 Japan

Phone: +81-3-5841-6106 Fax: +81-3-5841-6130

Email: tkoike@hydra.t.u-tokyo.ac.jp

#### DATE OF THIS DOCUMENT

02 Sep. 2004

## 1. 0 DATASET OVERVIEW

# 1.1 Introduction

To clarify the energy and water cycle in the Tibetan Plateau, it is important to understand the profile of the soil moisture content and surface temperature.

The purpose of SMTMS (Soil Moisture and Temperature Measurement System) observation is to monitor these values and develop the land surface process models and satellite-based soil moisture retrieval methods.

## 1.2 Time period covered by the data

Start: 1 October 2002, 00:00 End: 31 March 2003, 23:00

## 1.3 Temporal characteristics of the data

All parameters are recoded every hour.

## 1.4 Physical location of the measurement

Latitude : 31.36866 N Longitude : 91.89871 E Elevation : 4509.2 m a.s.l. Landscape : Bare land (with the thin weed-like plant)

Canopy height: Less than 5cm.

Soil Characteristics: Sand

#### 1.5 Data source

#### 1.6 Website address references

http://monsoon.t.u-tokyo.ac.jp/camp/tibets/

#### 2.0 INSTRUMENTATION DESCRIPTION

## 2.1 Platform

The sensors are mounted on several heights.

## 2.2 Description of the instrumentation

Parameter	Model	Manufacturer
Soil Temperature	Pt100	Datamark
Soil Moisture	Trime EZ	Imko

## 2.3 Instrumentation specification

Soil Temp 4cm: Soil Temperature at the 4cm depth (deg.C) Soil Temp 20cm: Soil Temperature at the 20cm depth (deg.C) Soil Temp 40cm: Soil Temperature at the 40cm depth (deg.C) Soil Temp 60cm : Soil Temperature at the 60m depth (deg.C) Soil Temp 80cm: Soil Temperature at the 80cm depth (deg.C)

Soil Temp\_100cm : Soil Temperature at the 100cm depth (deg.C) Soil Temp\_130cm
Soil Temp\_160cm
Soil Temp\_160cm
Soil Temp\_200cm
Soil Temp\_250cm
Soil Temp\_250cm
Soil Moist 4cm
Soil Temperature at the 160cm depth (deg.C)
Soil Temperature at the 200cm depth (deg.C)
Soil Temperature at the 250cm depth (deg.C)
Soil Moist 4cm

Soil Moist 4cm : Soil Moisture at the 4cm depth (%)

Soil Moist 20cm : Soil Moisture at the 20cm depth (%) Soil Moist 60cm: Soil Moisture at the 60cm depth (%)

Soil Moist 100cm : Soil Moisture at the 100cm depth (%) Soil Moist\_160cm : Soil Moisture at the 160cm depth (%) Soil Moist\_210cm : Soil Moisture at the 210cm depth (%)

## 3.0 DATA COLLECTION AND PROCESSING

## 3.1 Description of data collection

Data are downloaded from the SMTMS twice a year. Then, data are sent to Tokyo, where they are processed.

## 3.2 <u>Description of derived parameters and processing techniques used</u>

Soil moisture and temperature are measured by using Trime MUX and Pt100 sensor.

Trime MUX is applied to TDR(Time Domein Reflectmetry) method. The principle of the TDR is based on measuring the propagation time of an electromagnetic pulse along measuring pins in the sample. The propagation time depends on the humidity content of the medium to be measured.

# **4.0 QUALITY CONTROL PROCEDURES**

For all parameters, the data has been visually checked, looking for extremely and unusual low/high values and/or periods with constant values thorough the CAMP Quality Control Web Interface.

The quality control flags follow the CEOP data flag definition document.

#### 5.0 GAP FILLING PROCEDURES

No gap filling procedure was applied.

#### **6.0 DATA REMARKS**

- 6.1 PI's assessment of the data
- 6.1.1 <u>Instruments problems</u>

None.

- 6.1.2 Quality issues
- 6.2 Missing data periods

None

#### 7.0 REFERENCE REQUIREMENTS

Original data was collected and is provided within the framework of GAME/CAMP Tibet Scientific and Technological Research Project, funded by the Ministry of Education, Culture, Sports, Science and Technology; the Japan Science and Technology Agency; the Frontier Research System for Global Change; the Japan Aerospace Exploration Agency; the Chinese Academy of Sciences; and the Chinese Academy of Meteorological Sciences.

#### 8.0 REFERENCES

N. Hirose, T. Koike, and H. Ishidaira, 2002: Study on Spatially Averaged Evaporation under Soil Moisture Heterogeneity Affected by Permafrost Micro-topography. JMSJ, Vol.80. pp191-203.

N. Hirose and T. Koike, 2001: The effect of the soil moisture heterogeneity on the spatially averaged evaporation at the permafrost plain area in Tibetan Plateau, Proceedings of the Fifth International Study Conference on GEWEX in Asia and GAME, 655-660.

T. Koike, N. Hirose, H. Ishidaira, Y. Ding, Y. Shen, S. Wang, B. Ye and M. Yang, 2001b: Hydrological Variability in the Tibetan Permafrost, Proc. of the 2nd International Workshop on TIPEX/GAME-Tibet, Kunming, China.

#### **TITLE**

CAMP\_Tibet\_BJ-SMTMS\_20030401\_20030930.stm

#### **CONTACT**

Nozomu Hirose

Depertment of Civil Engneering, University of Tokyo 7-3-1 Hongo, Bunkyoku, Tokyo, 113-8656 Japan

Phone: +81-3-5841-6107 Fax: +81-3-5841-6130

Email: hirose@hydra.t.u-tokyo.ac.jp

Toshio Koike

Depertment of Civil Engneering, University of Tokyo 7-3-1 Hongo, Bunkyoku, Tokyo, 113-8656 Japan

Phone: +81-3-5841-6106 Fax: +81-3-5841-6130

Email: tkoike@hydra.t.u-tokyo.ac.jp

#### DATE OF THIS DOCUMENT

20 Apr. 2005

## 1. 0 DATASET OVERVIEW

# 1.7 Introduction

To clarify the energy and water cycle in the Tibetan Plateau, it is important to understand the profile of the soil moisture content and surface temperature.

The purpose of SMTMS (Soil Moisture and Temperature Measurement System) observation is to monitor these values and develop the land surface process models and satellite-based soil moisture retrieval methods.

## 1.8 Time period covered by the data

Start: 1 April 2003, 00:00

End: 30 September 2003, 23:00

## 1.9 Temporal characteristics of the data

All parameters are recoded every hour.

## 1.10 Physical location of the measurement

Latitude : 31.36866 N Longitude : 91.89871 E Elevation : 4509.2 m a.s.l. Landscape : Bare land (with the thin weed-like plant)

Canopy height: Less than 5cm.

Soil Characteristics: Sand

#### 1.11 Data source

#### 1.12 Website address references

http://monsoon.t.u-tokyo.ac.jp/camp/tibets/

#### 2.0 INSTRUMENTATION DESCRIPTION

## 2.1 Platform

The sensors are mounted on several heights.

## 2.2 Description of the instrumentation

Parameter	Model	Manufacturer
Soil Temperature	Pt100	Datamark
Soil Moisture	Trime EZ	Imko

## 2.4 Instrumentation specification

Soil Temp 4cm: Soil Temperature at the 4cm depth (deg.C) Soil Temp 20cm: Soil Temperature at the 20cm depth (deg.C) Soil Temp 40cm: Soil Temperature at the 40cm depth (deg.C) Soil Temp 60cm : Soil Temperature at the 60m depth (deg.C) Soil Temp 80cm: Soil Temperature at the 80cm depth (deg.C)

Soil Temp\_100cm
Soil Temp\_100cm
Soil Temp\_130cm
Soil Temp\_160cm
Soil Temp\_200cm
Soil Temp\_200cm
Soil Temp\_200cm
Soil Temp\_250cm
Soil Moist 4cm
Soil Temperature at the 100cm depth (deg.C)
Soil Temperature at the 160cm depth (deg.C)
Soil Temperature at the 200cm depth (deg.C)
Soil Temperature at the 250cm depth (deg.C)
Soil Moist 4cm

Soil Moist 4cm : Soil Moisture at the 4cm depth (%)

Soil Moist 20cm : Soil Moisture at the 20cm depth (%) Soil Moist 60cm: Soil Moisture at the 60cm depth (%)

Soil Moist\_100cm : Soil Moisture at the 100cm depth (%) Soil Moist\_160cm : Soil Moisture at the 160cm depth (%) Soil Moist\_210cm : Soil Moisture at the 210cm depth (%)

## 3.0 DATA COLLECTION AND PROCESSING

## 3.1 Description of data collection

Data are downloaded from the SMTMS twice a year. Then, data are sent to Tokyo, where they are processed.

## 3.2 <u>Description of derived parameters and processing techniques used</u>

Soil moisture and temperature are measured by using Trime MUX and Pt100 sensor.

Trime MUX is applied to TDR(Time Domein Reflectmetry) method. The principle of the TDR is based on measuring the propagation time of an electromagnetic pulse along measuring pins in the sample. The propagation time depends on the humidity content of the medium to be measured.

## 4.0 QUALITY CONTROL PROCEDURES

For all parameters, the data has been visually checked, looking for extremely and unusual low/high values and/or periods with constant values thorough the CAMP Quality Control Web Interface.

The quality control flags follow the CEOP data flag definition document.

#### 5.0 GAP FILLING PROCEDURES

No gap filling procedure was applied.

#### **6.0 DATA REMARKS**

- 6.1 PI's assessment of the data
- 6.1.1 <u>Instruments problems</u>

None.

6.1.2 Quality issues

## 6.2 Missing data periods

```
Soil Moisture 210cm
                         2003/9/16 4:00
Soil_Moisture_160cm
                         2003/9/16 4:00
Soil_Moisture_100cm
                         2003/9/16 4:00
Soil Moisture 60cm 2003/9/16 4:00
Soil Moisture 20cm 2003/9/16 4:00
Soil Moisture 4cm 2003/9/16 4:00
Soil Temperature 250cm
                         2003/9/16 4:00
Soil Temperature 200cm
                         2003/9/16 4:00
Soil_Temperature_160cm
                         2003/9/16 4:00
Soil Temperature 130cm
                         2003/9/16 4:00
Soil Temperature 100cm
                         2003/9/16 4:00
Soil Temperature 80cm
                         2003/9/16 4:00
Soil Temperature 60cm
                         2003/9/16 4:00
Soil Temperature 40cm
                         2003/9/16 4:00
Soil Temperature 20cm
                         2003/9/16 4:00
Soil Temperature 4cm
                         2003/9/16 4:00
```

#### 7.0 REFERENCE REQUIREMENTS

Original data was collected and is provided within the framework of GAME/CAMP Tibet Scientific and Technological Research Project, funded by the Ministry of Education,

Culture, Sports, Science and Technology; the Japan Science and Technology Agency; the Frontier Research System for Global Change; the Japan Aerospace Exploration Agency; the Chinese Academy of Sciences; and the Chinese Academy of Meteorological Sciences.

#### 8.0 REFERENCES

N. Hirose, T. Koike, and H. Ishidaira, 2002: Study on Spatially Averaged Evaporation under Soil Moisture Heterogeneity Affected by Permafrost Micro-topography. JMSJ, Vol.80. pp191-203.

N. Hirose and T. Koike, 2001: The effect of the soil moisture heterogeneity on the spatially averaged evaporation at the permafrost plain area in Tibetan Plateau, Proceedings of the Fifth International Study Conference on GEWEX in Asia and GAME, 655-660.

T. Koike, N. Hirose, H. Ishidaira, Y. Ding, Y. Shen, S. Wang, B. Ye and M. Yang, 2001b: Hydrological Variability in the Tibetan Permafrost, Proc. of the 2nd International Workshop on TIPEX/GAME-Tibet, Kunming, China.

#### **TITLE**

CAMP Tibet BJ-SMTMS 20031001 20040331.stm

#### **CONTACT**

Nozomu Hirose

Depertment of Civil Engneering, University of Tokyo 7-3-1 Hongo, Bunkyoku, Tokyo, 113-8656 Japan

Phone: +81-3-5841-6107 Fax: +81-3-5841-6130

Email: hirose@hydra.t.u-tokyo.ac.jp

Toshio Koike

Depertment of Civil Engneering, University of Tokyo 7-3-1 Hongo, Bunkyoku, Tokyo, 113-8656 Japan

Phone: +81-3-5841-6106 Fax: +81-3-5841-6130

Email: tkoike@hydra.t.u-tokyo.ac.jp

#### DATE OF THIS DOCUMENT

10 Jun. 2006

## 1. 0 DATASET OVERVIEW

# 1.13 Introduction

To clarify the energy and water cycle in the Tibetan Plateau, it is important to understand the profile of the soil moisture content and surface temperature.

The purpose of SMTMS (Soil Moisture and Temperature Measurement System) observation is to monitor these values and develop the land surface process models and satellite-based soil moisture retrieval methods.

## 1.14 Time period covered by the data

Start: 1 October 2003, 00:00 End: 31 March 2004, 23:00

# 1.15 <u>Temporal characteristics of the data</u>

All parameters are recoded every hour.

## 1.16 Physical location of the measurement

Latitude : 31.36866 N Longitude : 91.89871 E Elevation : 4509.2 m a.s.l.

: Bare land (with the thin weed-like plant) Landscape

Canopy height: Less than 5cm.

Soil Characteristics: Sand

# 1.17 Data source

#### 1.18 Website address references

http://monsoon.t.u-tokyo.ac.jp/camp/tibets/

#### 2.0 INSTRUMENTATION DESCRIPTION

## 2.1 Platform

The sensors are mounted on several heights.

## 2.2 Description of the instrumentation

Parameter	Model	Manufacturer
Soil Temperature	Pt100	Datamark
Soil Moisture	Trime EZ	Imko

## 2.5 Instrumentation specification

Soil Temp 4cm: Soil Temperature at the 4cm depth (deg.C) Soil Temp 20cm: Soil Temperature at the 20cm depth (deg.C) Soil Temp 40cm: Soil Temperature at the 40cm depth (deg.C) Soil Temp 60cm : Soil Temperature at the 60m depth (deg.C) Soil Temp 80cm: Soil Temperature at the 80cm depth (deg.C)

Soil Temp 100cm : Soil Temperature at the 100cm depth (deg.C) Soil Temp\_130cm
Soil Temp\_160cm
Soil Temp\_200cm
Soil Temp\_200cm
Soil Temp\_250cm
Soil Moist 4cm
Soil Temperature at the 160cm depth (deg.C)
Soil Temperature at the 200cm depth (deg.C)
Soil Temperature at the 250cm depth (deg.C)
Soil Moist 4cm
Soil Moisture at the 4cm depth (%)

Soil Moist 4cm : Soil Moisture at the 4cm depth (%)

Soil Moist 20cm : Soil Moisture at the 20cm depth (%) Soil Moist 60cm: Soil Moisture at the 60cm depth (%)

Soil Moist 100cm : Soil Moisture at the 100cm depth (%) Soil Moist\_160cm : Soil Moisture at the 160cm depth (%) Soil Moist\_210cm : Soil Moisture at the 210cm depth (%)

## 3.0 DATA COLLECTION AND PROCESSING

## 3.1 Description of data collection

Data are downloaded from the SMTMS twice a year. Then, data are sent to Tokyo, where they are processed.

## 3.2 <u>Description of derived parameters and processing techniques used</u>

Soil moisture and temperature are measured by using Trime MUX and Pt100 sensor.

Trime MUX is applied to TDR(Time Domein Reflectmetry) method. The principle of the TDR is based on measuring the propagation time of an electromagnetic pulse along measuring pins in the sample. The propagation time depends on the humidity content of the medium to be measured.

## 4.0 QUALITY CONTROL PROCEDURES

For all parameters, the data has been visually checked, looking for extremely and unusual low/high values and/or periods with constant values thorough the CAMP Quality Control Web Interface.

The quality control flags follow the CEOP data flag definition document.

#### 5.0 GAP FILLING PROCEDURES

No gap filling procedure was applied.

#### **6.0 DATA REMARKS**

- 6.1 PI's assessment of the data
- 6.1.1 <u>Instruments problems</u>

None.

6.1.2 Quality issues

None.

## 7.0 REFERENCE REQUIREMENTS

Original data was collected and is provided within the framework of GAME/CAMP Tibet Scientific and Technological Research Project, funded by the Ministry of Education, Culture, Sports, Science and Technology; the Japan Science and Technology Agency; the Frontier Research System for Global Change; the Japan Aerospace Exploration Agency; the Chinese Academy of Sciences; and the Chinese Academy of Meteorological Sciences.

#### 8.0 REFERENCES

N. Hirose, T. Koike, and H. Ishidaira, 2002: Study on Spatially Averaged Evaporation under Soil Moisture Heterogeneity Affected by Permafrost Micro-topography. JMSJ, Vol.80. pp191-203.

N. Hirose and T. Koike, 2001: The effect of the soil moisture heterogeneity on the spatially averaged evaporation at the permafrost plain area in Tibetan Plateau, Proceedings of the Fifth International Study Conference on GEWEX in Asia and GAME, 655-660.

T. Koike, N. Hirose, H. Ishidaira, Y. Ding, Y. Shen, S. Wang, B. Ye and M. Yang, 2001b: Hydrological Variability in the Tibetan Permafrost, Proc. of the 2nd International Workshop on TIPEX/GAME-Tibet, Kunming, China.

# 9.0 Missing Data Periods

None.