

# Flux Tower data measured at 20Hz and 1Hz provided by Dugway Proving Ground TEAST Tower Location 1

## T-EAST-LOCATION1

Author(s):	Regarding data questions contact:
Harindra Joseph S. Fernando Mailing address: 156 Fitzpatrick Hall of Engineering, Notre Dame, IN, USA, 46556 Tel./Fax.: 574-631-9346/ 574-631-9236, E-mail and web: <a href="mailto:Fernando.10@nd.edu">Fernando.10@nd.edu</a> , <a href="http://ceees.nd.edu/profiles/hfernando">http://ceees.nd.edu/profiles/hfernando</a>	Laura S. Leo / Zachariah Silver Mailing address: 156 Fitzpatrick Hall of Engineering, Notre Dame, IN, USA, 46556 Tel./Fax.: 574-631-8419/574-631-9236 E-mail and web: <a href="mailto:LauraSandra.Leo.13@nd.edu">LauraSandra.Leo.13@nd.edu</a> / <a href="mailto:zsilver@nd.edu">zsilver@nd.edu</a> , <a href="https://engineering.nd.edu/profiles/lleo">https://engineering.nd.edu/profiles/lleo</a> / <a href="https://engineering.nd.edu/profiles/zsilver">https://engineering.nd.edu/profiles/zsilver</a>

### 1.0 Data Set Overview

#### 1.1 Time period covered by the data

Approximately May 2013. For specific times please refer to individual file names.

#### 1.2 Physical location (latitude, longitude, elevation)

40.11436, -113.23892, 1343.38

#### 1.3 Instrument type

Flux Tower

#### 1.4 Data provider

Dugway Proving Ground, University of Notre Dame

#### 1.5 Web address references

<http://www3.nd.edu/~dynamics/materhorn/>

[https://www.eol.ucar.edu/field\\_projects/materhorn-x](https://www.eol.ucar.edu/field_projects/materhorn-x)

### 2.0 Instrument Description

Surface tower including five RM Young Ultrasonic 81000 anemometers mounted at 2m, 4m, 8m, 16m and 32m above ground level. Also included are Temperature Relative Humidity Measurements, Barometric Pressure, and Thermocouples. (Sonic coordinates rotated 180 degrees)



## 2.1 Instrument website

<http://www.alumatower.com/>, (Aluminum Tower)

<https://www.campbellsci.com/cr3000>, (CR3000 Datalogger)

<https://s.campbellsci.com/documents/us/manuals/loggernet.pdf>

TOA5 file format description (Appendix B, pages: B-4, B-3)

<https://www.campbellsci.com/hmp45c-1>, (Temperature / Relative Humidity Probe)

<https://www.campbellsci.com/cs106>, (Barometer)

<http://www.youngusa.com/products/6/3.html>, (RM Young 81000)

<http://www.omega.com/pptst/5TC.html>, (Thermocouples 5TC-GG-K-36-36)

## 2.2 Table of specifications

Accuracy	Range	Frequency	Resolution
See individual instrument websites	See individual instrument websites	See individual instrument websites	See individual instrument websites

## 3.0 Data Collection and Processing

### 3.1 Description of data collection

### 3.2 Description of derived parameters and processing techniques used

Original data files are provided.

### 3.3 Description of quality assurance and control procedures

This dataset was not subject to any quality control or processing it has been provided in its original form.

### 3.4 Data intercomparisons

## 4.0 Data Format

### 4.1 Data file structure

TOA5, (ASCII csv with header)

### 4.2 File naming convention

dataProvider\_instrument[\_identifier]\_rate\_instrumentType\_startDateAndTime\_endDateAndTime.extension

### 4.3 Data format

comma delimited ASCII

### 4.4 Data layout

Each file has four header lines. First header line contains information on the logger and the consecutive three lines provides the column headers (variables, units and measurement types) for all subsequent rows of data contained within the file.

### 4.5 List of parameters with units, sampling intervals, frequency, range

Variable names usually contain the variable type and the height of the measurement in meters. 05 refers to a measurement taken at 0.5m. As an example u16 means "u" wind component measured at 16 m.

#### **4.6 Data version number and date**

raw, v1.0, October 2016

#### **4.7 Description of flags, codes used in the data, and definitions**

#### **4.8 Data sample**

The data sample is provided in the Filtered\_Headers.txt. Please look for the file name in the Filtered\_Headers.txt for the corresponding data sample.

#### **5.0 Data Remarks**

##### **5.1 PI's assessment of the data**

- 1) The sonic anemometers might have been reversed.
- 2) For the U and V wind components' direction, please consult the sensor's reference manual.
- 3) The tower was moved on 22 of May 2013, at 8AM local time.
- 4) Further notes (when available) for each recorded period is in the records.xlsx file.

##### **5.2 Missing data periods**

##### **5.3 Software compatibility**

#### **6.0 References**

- [1] Fernando, H. J. S., E. R. Pardyjak, S. Di Sabatino, F. K. Chow, S. F. J. DeWekker, S. W. Hoch, J. Hacker, J. C. Pace, T. Pratt, Z. Pu, J. W. Steenburgh, C. D. Whiteman, Y. Wang, D. Zajic, B. Balsley, R. Dimitrova, G. D. Emmitt, C. W. Higgins, J. C. R. Hunt, J. G. Knievel, D. Lawrence, Y. Liu, D. F. Nadeau, E. Kit, B. W. Blomquist, P. Conry, R. S. Coppersmith, E. Creegan, M. Felton, A. Grachev, N. Gunawardena, C. Hang, C. M. Hocut, G. Huynh, M. E. Jeglum, D. Jensen, V. Kulandaivelu, M. Lehner, L. S. Leo, D. Liberzon, J. D. Massey, K. McEnerney, S. Pal, T. Price, M. Sghiatti, Z. Silver, M. Thompson, H. Zhang, T. Zsedrovits, 2015: The MATERHORN – Unraveling the Intricacies of Mountain Weather, BAMS, doi: <http://dx.doi.org/10.1175/BAMS-D-13-00131.1>.